
Accotex





Elastomer Expertise

Accotex, the world's leading supplier of cots and aprons for the textile industry, is a subsidiary of the Rieter Group. Based in Muenster (Germany), Accotex creates customer value through system expertise, innovative solutions, after-sales excellence and a global presence. The leading position of Accotex cots and aprons is based on more than 100 years of elastomer expertise. The products are used, for example, in short and long staple spinning, rotor and air-jet spinning, and twisting.

Elastomer components by Accotex enable consistently high yarn quality in all process steps, resulting in a better fabric quality. The development team is continuously working on new elastomer compounds for even better results in the textile industry. Accotex aims to fulfil customers' needs with constant product quality in every order. Worldwide teams support customers in all matters around Accotex cots and aprons.

Accotex completes its extensive portfolio with the addition of DAYTEX, a leading manufacturer of shrinkage belts in the finishing as well as cots and aprons and texturing sector. Multinational teams are responsible for the development, manufacturing and distribution of DAYTEX products. A network of experienced representatives around the globe provides the highest level of service and expertise to ensure the optimal performance of our products.

4	Outstanding advantages				
6	Cots				
8	Apro	ns			
10	Shor	t staple spinning			
	10	Spinning preparation			
	12	Ring- and compact spinning			
	14	Air-jet spinning			
	16	Rotor spinning			
18	Long-staple spinning				
	18	Spinning preparation			
	20	Ring spinning			
22	Twis	ting			
23	Glass fiber spinning				
24	Accotex DAYTEX				
27	Accessory				

Outstanding advantages

OUTSTANDING

Elastomer Components

Highest Product Reliability

By using high quality, reliable and stable raw materials, the highest possible product reliability is achieved.

Perfect Running Behaviour

Perfect running behavior is characterized by fewer laps, fewer end breaks and fewer unbound fibers.




State-of-the-Art Production Facility

Stable compound quality from shipment to shipment due to highest sophisticated mixing technology.

Outstanding Life Time

Resistance to all common fiber finishes, paints and greases, as well as various climatic conditions over the entire service life.



Cots

Accotex Cots distinguish by an excellent performance and thus guarantee the production of a stable yarn quality over the whole cot lifetime. The perfect running behaviour is featured by less laps, less end breaks and less unbound fibers. All these properties result into less machine standstills over the cot life, which guarantees highest machine efficiency.

Quality standard

The highest product reliability is characterized by the outstanding product quality, which comes along with the usage of reliable and stable raw materials.

Area of application

Accotex Cots are designed to meet the demands of all fibers and do perform best even under different climate conditions.

Manufacturing expertise

The state-of- the-art production facility with its newest sophisticated mixing technologies enables a stable compound quality from shipment to shipment.



Types, sizes and surfaces

Pressfit cots are an invention by Accotex. They run virtually tension free, providing high performance and long durability.

Accosmart, the special cot concept, guarantees high and constant yarn quality with longer service life between the single grinding cycles.

Reinforced cots are used in applications where roller diameter or roller tolerance does not permit the use of Pressfit cots.

At a glance

- Excellent cot performance and thus stable yarn quality over the whole cot life
- Less laps, less end breaks, less unbound fibers Less machine stand stills over cot life means higher efficiency
- Usage of highest quality, reliable and stable raw materials
- Processing of all types of fibers under different climate conditions
- Stable compound quality from shipment to shipment due to highest sophisticated mixing technology
- perfect grindability



Aprons

Accotex Aprons distinguish by a perfect running behaviour, which comes along with good friction properties over the whole apron life time. Further Accotex Aprons are running vibration free, with highest possible crack resistance and lowest slippage tendency. Even apron breakages are very low for Accotex Aprons, which results into less downtime for the single spindle position.



The Standard

All these features result into less machine standstills or interruptions, which guarantees highest possible machine efficiency.

Area of application

All in all Accotex Aprons stand for a trouble free processing of all common fibers and under various climate conditions.

Manufacturing expertise

Highest compound technology combined with high-tech chemistry, selected high quality raw materials and state-of-the-art production facility with newest mixing technology results into highest product reliability.

Product promise

Precise product dimensions and highest dimensional stability characterize Accotex Aprons. The stable and consistent construction of the Accotex Aprons is the key for superior life cycles for all common fibers. Sufficient resistance to all popular fibre dressings, colours and greases comes along.

Types, sizes and surfaces

Accotex Aprons are available in a wide range of dimensions. Certain common sizes are even available with a knurled inside structure. Skived or skived and pre-glued versions are available in a wide range of dimensions.

What to expect

- Good friction properties and running behaviour over the whole apron life
- No vibration, no stress cracking, lowest slippage tendency
- Less breakages less downtime of single spindles
- Less machine stand stills or interruptions higher efficiency
- Trouble free processing of all common fibers under different climate conditions
- Highest compound technology and high-tech chemistry due to perfect raw material selection and sophisticated and consistent mixing technology
- · Precise product dimension
- High dimensional stability
- Stable and consistent construction
- Superior life cycle for all common fibre types
- Sufficient resistance to all popular fibre dressings, colours and greases
- · Skived or skived and pre-glued versions
- · Certain sizes with knurled inner layer



Short-Staple Ring Spinning

Spinning preparation



Drawing







	*			
Type and/or application	Draw frame roller cot	Draw frame roller cot	Draw frame roller cot	
Fibers	Co	Co Blends MMF	Blends MMF	
Product Color Shore A hardness	121 black 70	J-470 green 70	NO-714 light green 80	





Type and/or application	Draw frame roller cot	Clearer tubes	
Fibers	Co Blends MMF	All	
Product Color Shore A hardness	J-490 gray 83	NO-780P gray	

Combing



Type and/or application	Detaching roller cot	Detaching roller cot	
Fibers	Со	Со	
	Blends	Blends	
	MMF	MMF	
Product Color Shore A hardness	J-463 lavender 63	J-470 green 70	





Type and/or application	Drafting unit roller cot	Drafting unit roller cot	
Fibers	Со	Со	
	Blends	Blends	
	MMF	MMF	
		Wo	
Product Color Shore A hardness	J-476 blue 76	J-490 gray 83	

Roving





Type and/or application	Front roller cot	Front and back roller cot	
Fibers	Co	Со	
	Blends	Blends	
	MMF	MMF	
Product Color Shore A hardness	J-476 blue 76	J-490 gray 83	_







Type and/or application	Top and bottom apron	Top and bottom apron	Apron cradle roller cot
Fibers	All	All	Co
			Blends
			MMF
Product Color Shore A hardness	NO-78210G, gray/green	NO-78210GX gray/gray	ME-480 black 80

Short-Staple Spinning

Ring- and compact spinning



Compact spinning



Type and/or application	Compact apron
Fibers	All
Product Color Shore A hardness	LongLife gray/gray







Type and/or application	Front roller cot Compact applications	Front roller cot, Compact + conventional applications, medium counts	Front and back roller cot for all applications, medium coarse counts
Fibers	Co (combed)	All	All
Product Color	Accosmart AS-6 lavender	Accosmart AS-7 green	Accosmart AS-8 blue
Shore A hardness	Working layer equals to 63 Shore A	Working layer equals to 70 Shore A	Working layer equals to 76 Shore A

Ring spinning







Type and/or application	Front roller cot		Front roller cot		Front roller cot	
Fibers	Co (combed)	≥ Ne 60	Co (combed)	≥ Ne 30	Co (carded and combed)	≥ Ne 18
			Blends	≥ Ne 40	Blends	≥ Ne 20
			MMF	≥ Ne 50	MMF	≥ Ne 30
Product Color Shore A hardness	J-460 burgundy 60		J-463 lavender 63		J-465 turquoise 65	







Type and/or application	Front roller cot		Front and back roller cot		Front and back roller cot	
Fibers	Blends	≥ Ne 30 ≥ Ne 30	Co (carded) Blends MMF	≥ Ne 20 ≥ Ne 30 ≥ Ne 30	Co (carded) Blends MMF	≥ Ne 10 ≥ Ne 18 ≥ Ne 18
Product Color Shore A hardness	J-468 brown 68		J-470 green 70		J-476 blue 76	







Type and/or application	Front and back roller cot for general purpose	Top and bottom apron	Top and bottom apron
Fibers	All	All	All
Product Color Shore A hardness	J-490 gray 83	NO-79201 gray/blue	NO-79201 knurled gray/blue







Type and/or application	Top and bottom apron	Top and bottom apron	Top and bottom apron
Fibers	All	All	All
Product Color	NO-78210GX gray/gray	NO-78210G gray/green	NO-78210G¹ gray/green

 $^{\rm 1}\,\text{knurled}$ version available with 72.5/76.3/79.0 mm inner diameter



Type and/or application	Apron cradle roller cot
Fibers	All
Product Color Shore A hardness	ME-480 black 80

Short-Staple Spinning

Air-jet spinning



Air-jet spinning





Type and/or application	Front roller	Front roller cot	
Fibers	Со	Co	
	Blends	Blends	
	MMF	MMF	
Product Color Shore A hardness	J-490 S ² reddish brown 72	J-476 ² blue 76	







Type and/or application	Front roller cot	Apron cradle roller cot	Back roller cot	
Fibers	Co	Co	Co	
	Blends	Blends	Blends	
	MMF	MMF	MMF	
Product Color Shore A hardness	J-490 ² gray 83	118 dark gray 72	J-490 gray 83	







Type and/or application	Top and bottom apron	Top apron	Bottom apron
Fibers	100% Co Blends	Co Blends MMF	CV, PES or other MMF Blends
Product Color	NO-4970 KN gray/green	NO-6270 KN blue/green	NO-9670 KN black/green

² Bridge length: MMF 15.8 mm Blends: 17.8 mm CO: 21.8 mm 2nd OD: 25.0 mm

Short-Staple Spinning

Rotor spinning










Type and/or application	Nip roller cot	Nip roller cot	Nip roller cot	
Fibers	Co Blends MMF	Blends MMF	All	
Product Color Shore A hardness	121 black 70	118 dark gray 72	J-490 gray 83	



Long-Staple Spinning

Spinning preparation



Blending & Drawing



Type and/or application	Front and back roller cot	
Fibers	Wo Blends MMF	
Product Color Shore A hardness	J-490 EasyFit gray 83	

Wo Wool MMF Manmade fibers

Finisseur







Type and/or application	Front and back roller cot	Front and back roller cot	Top and bottom apron cot
Fibers	Wo	Wo	Wo
	MMF	Blends	Blends
		MMF	MMF
Product Color Shore A hardness	J-470 green 70	J-490 gray 83	NO-78210X gray/dark-gray

Roving







Type and/or application	Front and back roller cot	Apron roller cot	Top and bottom apron
Fibers	Wo Blends MMF	Wo	All
Product Color Shore A hardness	1-490 grav 83	ME-480 black 80	NO-78210GX grav/grav



Type and/or application	Top and bottom apron
Fibers	All
Product Color	NO-79201 knurled gray/blue

Ballon cots



Type and/or application	Balloon cot
Fibers	All
Product Color	NO-780B³ gray

³ Wall thickness (mm): 1.7, 2.0, 2.2, 2.5

Wo Wool **MMF** Manmade fibers

Long-Staple Spinning

Ring spinning



Ring spinning







Type and/or application	Front roller cot		Front roller cot	Front roller cot	
Fibers	Wo	≥ Ne 80	Wo	Wo Blends MMF	
Product Color Shore A hardness	J-460 burgundy 60		J-463 lavender 63	J-470 green 70	







Type and/or application	Front roller cot		Back roller cot	Apron roller cot	
Fibers	Wo		Wo	All	
	Blends	≥ Ne 30	Blends		
		≥ Ne 30	MMF		
Product Color Shore A hardness	J-476 blue 76		J-490 gray 83	ME-480 black 80	



Type and/or application	Compact apron	
Fibers	All	
Product Color Shore A hardness	LongLife gray/gray	







Type and/or application	Top and bottom apron	Top and bottom apron	Balloon Cot
Fibers	All	All	All
Product Color	NO-78210GX gray/dark-gray	NO-79201 gray/blue	NO-780B³ gray

³ Wall thickness (mm): 1.7, 2.0, 2.2, 2.5

Wo Wool MMF Manmade fibers

Twisting







Type and/or application	Twister Cot	Sleeve
Fibers	All	All
Product Color Shore A hardness	J-490 gray 83	TW-450X gray/gray 65

Glass Fiber Spinning









Type and/or application	Glass forming apron	Glass forming apron	Glass forming apron
Fibers	Coarse	Fine	Ultra fine
Product Color Shore A hardness	546 black 1-2 μRa	546 FG black <= 0.85 μRa	546 FG3 black ≤ 0,5 μRa

Accotex DAYTEX







Type and/or application	Texturing cot	Texturing cot
Fibers	All MMF	All MMF
Product Color Shore A hardness	836 gray 75	121 black 70





Type and/or application	Texturing apron	Texturing apron	
Fibers	All MMF	All MMF	
Product Color	203 T gray/light gray	T-4347 red/gray	

MMF Manmade fibers

Accotex DAYTEX

Roll coverings



Compound	Cork & rubber	Cork & rubber	Cork & rubber
Backing Surface Finish	Co Smooth	Co Smooth	Co+PES Smooth
Product Color Shore A hardness	DK153 with PSA black 45 +/- 10	DK154 (without PSA) black 45 +/- 10	DK107 tan 45 +/- 10
Compound	Nitrile rubber	Nitrile rubber	Carboxylated rubber
Backing Surface Finish	Co Smooth	Co Sand finish	Co + PES Sand finish
Product Color Shore A hardness	NO732 gray 42 +/- 5	SF150 orange 60 +/- 5	G520 white 75 +/- 5
		100	
Compound	Carboxylated rubber	Natural rubber	Natural rubber
Backing Surface Finish	Co + PES Rough top	Co Smooth	Co + PES Embossed
Product Color Shore A hardness	G330 gray/yellow 65 +/- 5	G530 tan 45 +/- 5	G530E tan 45 +/- 5
			A second
Compound	PVC	Nitrile rubber	Nitrile rubber
Backing Surface Finish	Co + PES Smooth	Co + PES Sand finish	Co + PES Smooth
Product Color Shore A hardness	BR14 light blue 72 +/- 5	G320 blue 60 +/- 5	G310 dark blue 65 +/- 5
Compound	Nitrile rubber	Natural rubber	
Backing Surface Finish	Co + PES Rough top	Co + PES Rough top	
Product Color Shore A hardness	G310E dark blue 65 +/- 5	SF150 tan 39 +/- 5	Co Cotton PES Polyester

Accotex DAYTEX

Sanforizing





Type and/or application	Shrinkage belt		
Fibers	From heavy to light fabric including comfit and knitted goods		
Product Color Shore A hardness	DAYTEX 768 light tan 38 - 40		

Accessory

